

View Online at <https://aerobasegroup.com/nsn/5306-01-203-0215>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.938 inches

**Fastener Length:**

Between 1.688 inches and 1.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.4280 inches and 0.4375 inches

**Hole Diameter:**

Between 0.0605 inches and 0.0685 inches

**Locking Feature:**

Patch threads or strip threads

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c fastener and 38.0 rockwell c fastener

**Hole Configuration Style:**

Hexagon flats

**Material:**

Steel fastener

**Material Specification:**

Sae j429 grade 8 assn standard single material response fastener

**Surface Treatment:**

Zinc fastener and chromate fastener

**Surface Treatment Specification:**

Astm b633 type 2 sc 3 assn standard single treatment response fastener

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style and 8 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0