Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-203-0215



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.750 inches and 0.938 inches Fastener Length: Between 1.688 inches and 1.750 inches **Head Style:** Hexagon **Head Height:** Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.4280 inches and 0.4375 inches Hole Diameter: Between 0.0605 inches and 0.0685 inches Locking Feature: Patch threads or strip threads **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener Hole Configuration Style: Hexagon flats Material: Steel fastener **Material Specification:** Sae j429 grade 8 assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener

1

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

NSN 5306-01-203-0215

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style and 8 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

