

View Online at <https://aerobasegroup.com/nsn/5306-01-203-0899>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.568 inches and 0.618 inches

**Fastener Length:**

Between 1.078 inches and 1.108 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.266 inches and 0.286 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

**Extended Washer Thickness:**

Between 0.072 inches and 0.092 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Surface Finish:**

32.0 microinches grip

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0