## NSN 5306-01-203-0899

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-203-0899

view Offilite at https://aerobasegroup.com/nsn/3300-01-203-0
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.568 inches and 0.618 inches
Fastener Length:
Between 1.078 inches and 1.108 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.266 inches and 0.286 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.072 inches and 0.092 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-203-0899

Shear Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0