## NSN 5306-01-203-0900

Shear Bolt - Page 1 of 2

Between 0.375 inches and 0.405 inches

Between 0.813 inches and 0.843 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

**Head Style:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-203-0900

Double hexagon extended washer
Head Height:
0.196 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.340 inches and 0.350 inches
Extended Washer Thickness:
0.064 inches
Hole Diameter:
Between 0.034 inches and 0.042 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
0.438 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate

## NSN 5306-01-203-0900

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Suriace	Healineil	Specification.

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0