## NSN 5306-01-203-1590

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-203-1590 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.370 inches and 0.390 inches **Fastener Length:** 1.000 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **First Diameter From Head:** Between 0.141 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.610 inches and 0.630 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5306-01-203-1590

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0