## NSN 5306-01-203-7568

Machine Bolt - Page 1 of 2

Between 0.619 inches and 0.750 inches

Between 0.719 inches and 0.750 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

**Head Style:** Hexagon

2a



View Online at https://aerobasegroup.com/nsn/5306-01-203-7568

Head Height:
Between 0.150 inches and 0.163 inches
Width Between Flats:
Between 0.4280 inches and 0.4375 inches
Hole Diameter:
Between 0.0605 inches and 0.0685 inches
Locking Feature:
Patch threads or strip threads
Thread Diameter:
0.250 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
32.0 rockwell c fastener and 38.0 rockwell c fastener
Hole Configuration Style:
Hexagon flats
Material:
Steel fastener
Material Specification:
Sae j429 grade 8 assn standard single material response fastener
Surface Treatment:
Zinc fastener and chromate fastener
Surface Treatment Specification:
Astm b633 type 2 sc 3 assn standard single treatment response fastener

## NSN 5306-01-203-7568

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unc
Specification Or Standard:
2 type and 10p style and 8 grade
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0