

View Online at <https://aerobasegroup.com/nsn/5306-01-203-8353>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.899 inches and 0.939 inches

Fastener Length:

2.169 inches

Head Style:

Double hexagon extended washer

Head Height:

0.618 inches

Width Between Flats:

0.687 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

0.150 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp 6150

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or mil-s-8503 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

96906-ms21250-10020 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.