

View Online at <https://aerobasegroup.com/nsn/5306-01-204-6843>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.526 inches and 0.556 inches

Fastener Length:

Between 0.888 inches and 0.938 inches

Head Style:

Undercut hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

End Application:

Used on sentry f22 aircraft

Thread Diameter:

0.500 inches

Grip Length:

Between 0.362 inches and 0.382 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

140000 pounds per square inch

Product Name:

Bolt hx hd

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.