

View Online at <https://aerobasegroup.com/nsn/5306-01-205-2809>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.618 inches and 0.668 inches

Fastener Length:

Between 0.878 inches and 0.908 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.312 inches and 0.332 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0