NSN 5306-01-205-3406

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-205-3406 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.824 inches and 0.874 inches **Fastener Length:** Between 4.896 inches and 4.926 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.547 inches and 0.567 inches Width Between Flats: 1.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches **Shoulder Diameter:** 0.592 inches first shoulder and 0.593 inches first shoulder **Shoulder Length:** 4.052 inches first shoulder and 4.072 inches first shoulder **Thread Diameter:** 0.562 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-205-3406

Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0