## NSN 5306-01-205-5907

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-205-5907 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 1.132 inches and 1.162 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.265 inches and 0.285 inches Width Between Flats: 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Shoulder Diameter:** 0.217 inches first shoulder and 0.218 inches first shoulder **Shoulder Length:** 0.740 inches first shoulder and 0.760 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf Shelf Life: N/a

## NSN 5306-01-205-5907

Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0