NSN 5306-01-205-5914

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-205-5914 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.413 inches and 0.463 inches **Fastener Length:** Between 1.173 inches and 1.203 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.740 inches and 0.760 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:**

Hexagon corners

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

NSN 5306-01-205-5914

Shear Bolt - Page 2 of 2



Spe	cific	ation	Data:
-----	-------	-------	-------

80205-nas6305 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0