## NSN 5306-01-205-8016 Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-205-8016
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 0.535 inches and 0.545 inches
Head Diameter:
Between 0.495 inches and 0.505 inches
Head Height:
Between 0.140 inches and 0.150 inches
Shank Unthreaded Hole Diameter:
0.081 inches first hole and 0.086 inches first hole
First Diameter From Head:
Between 0.165 inches and 0.170 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.135 inches and 0.145 inches
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
32
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.330 inches first hole and 0.340 inches first hole
Externally Relieved Body Diameter Quantity:
1
Special Features:
Slotted head
Material Specification:
Ams 5613 assn standard single material response
Surface Treatment:
Cadmium
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0