

View Online at <https://aerobasegroup.com/nsn/5306-01-205-8016>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.450 inches

**Fastener Length:**

Between 0.535 inches and 0.545 inches

**Head Diameter:**

Between 0.495 inches and 0.505 inches

**Head Height:**

Between 0.140 inches and 0.150 inches

**Shank Unthreaded Hole Diameter:**

0.081 inches first hole and 0.086 inches first hole

**First Diameter From Head:**

Between 0.165 inches and 0.170 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.135 inches and 0.145 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.330 inches first hole and 0.340 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Slotted head

**Material Specification:**

Ams 5613 assn standard single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0