NSN 5306-01-205-9155

Shear Bolt - Page 1 of 2



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.320 inches and 0.370 inches
Fastener Length:
Between 1.142 inches and 1.172 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
Surface Finish: 32.0 microinches threads
32.0 microinches threads
32.0 microinches threads Material:
32.0 microinches threads Material: Iron alloy 660
32.0 microinches threads Material: Iron alloy 660 Material Specification:
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6703 professional/industrial association standard

NSN 5306-01-205-9155

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0