

View Online at <https://aerobasegroup.com/nsn/5306-01-206-5179>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.589 inches and 0.639 inches

**Fastener Length:**

Between 1.661 inches and 1.691 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.273 inches and 0.293 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Head Minor Diameter:**

Between 0.448 inches and 0.455 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.052 inches and 1.072 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0