## NSN 5306-01-206-7225

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-206-7225 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.650 inches **Fastener Length:** 1.120 inches **Head Style:** Hexagon **Head Height:** Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches **First Diameter From Head:** Between 0.365 inches and 0.370 inches **Second Diameter From Head:** Between 0.240 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.345 inches and 0.355 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.470 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 33.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-01-206-7225

Externally Relieved Body Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0