## NSN 5306-01-206-7226

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-206-7226

View Online at https://aerobasegroup.com/nsn/5306-01-206-7226
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.428 inches and 0.478 inches
Fastener Length:
Between 1.376 inches and 1.406 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
renene en englis (per).
160000 pounds per square inch
- · · ·
160000 pounds per square inch
160000 pounds per square inch  Hardness Rating:
160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2 cl 2 federal specification single treatment response
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator: Unjf
160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches threads  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator:  Unjf  Specification Data:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator: Unjf  Specification Data: 80205-nas1108 professional/industrial association standard
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches threads  Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator: Unjf  Specification Data: 80205-nas1108 professional/industrial association standard  Shelf Life:

--

## NSN 5306-01-206-7226

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0