

View Online at <https://aerobasegroup.com/nsn/5306-01-207-0196>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.443 inches and 0.493 inches

**Fastener Length:**

Between 1.140 inches and 1.170 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.290 inches and 0.310 inches

**Width Between Flats:**

0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.438 inches

**Extended Washer Thickness:**

Between 0.059 inches and 0.079 inches

**Shoulder Diameter:**

0.280 inches first shoulder and 0.281 inches first shoulder

**Shoulder Length:**

0.677 inches first shoulder and 0.697 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.948 inches first hole and 0.988 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0