NSN 5306-01-207-3020

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-207-3020

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.009 inches |
| Fastener Length: |
| Between 1.744 inches and 1.774 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| Between 0.701 inches and 0.722 inches |
| Width Between Flats: |
| Between 0.803 inches and 0.814 inches |
| Extended Washer Diameter: |
| 0.917 inches |
| Extended Washer Thickness: |
| Between 0.168 inches and 0.188 inches |
| Thread Diameter: |
| 0.750 inches |
| Thready Qty Per Inch (tpi): |
| 16 |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |