NSN 5306-01-207-6974

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-207-6974 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.410 inches and 0.440 inches **Fastener Length:** Between 1.462 inches and 1.512 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel **Material Specification:** Mil-b-7838 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1224 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-207-6974

Shear Bolt - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-7838 spec.