NSN 5306-01-207-7535

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-207-7535



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.568 inches and 0.618 inches Fastener Length: Between 1.078 inches and 1.108 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.290 inches and 0.319 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.040 inches and 0.060 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.490 inches and 0.510 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 200000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:**

Ams 5737 assn standard single material response

NSN 5306-01-207-7535

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0