NSN 5306-01-207-7536

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-207-7536

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.808 inches and 0.858 inches
Fastener Length:
Between 2.318 inches and 2.348 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.375 inches and 0.435 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
Between 0.089 inches and 0.109 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
200000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ama F707 acon standard single material

Ams 5737 assn standard single material response

NSN 5306-01-207-7536

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: