NSN 5306-01-207-9320

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-207-9320 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 1.007 inches and 1.037 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.265 inches and 0.285 inches Width Between Flats: Between 0.241 inches and 0.261 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Shoulder Diameter:** 0.2177 inches and 0.2182 inches first shoulder **Shoulder Length:** 0.615 inches and 0.635 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-207-9320 Shoulder Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A003b0