## NSN 5306-01-208-1952

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-208-1952

view Online at https://aerobasegroup.com/nsn/5306-01-208-1952
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.618 inches and 0.668 inches
Fastener Length:
Between 1.128 inches and 1.158 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.340 inches and 0.388 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-208-1952

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0