NSN 5306-01-208-5226

Shear Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-01-208-5226



3a **Thread Direction: Right-hand Thread Length:** Between 1.169 inches and 1.219 inches Fastener Length: Between 3.929 inches and 3.959 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.798 inches and 0.818 inches Width Between Flats: Between 0.934 inches and 0.943 inches **Extended Washer Diameter:** Between 1.428 inches and 1.438 inches **Extended Washer Thickness:** Between 0.325 inches and 0.345 inches **Grip Diameter:** Between 0.8730 inches and 0.8740 inches **Thread Diameter:** 0.875 inches Grip Length: Between 2.740 inches and 2.760 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Surface Finish: 32.0 microinches grip Material: Steel comp 8735 **Material Specification:** Mil-s-6098 military specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf **Specification Data:** 80205-nas634 professional/industrial association standard

NSN 5306-01-208-5226

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6098 spec.

