NSN 5306-01-208-6705

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-208-6705 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.526 inches and 0.576 inches **Fastener Length:** Between 1.724 inches and 1.754 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: Between 0.366 inches and 0.386 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Shoulder Diameter:** 0.3427 inches and 0.3432 inches first shoulder **Shoulder Length:** 1.178 inches and 1.198 inches first shoulder **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-208-6705

Shoulder Bolt - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0