

View Online at <https://aerobasegroup.com/nsn/5306-01-209-4087>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.340 inches and 0.350 inches

Fastener Length:

Between 1.955 inches and 1.985 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Hole Diameter:

Between 0.046 inches and 0.056 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Hexagon corners

Special Features:

No drills in head

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6603 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.