## NSN 5306-01-209-7163

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-209-7163

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

1.290 inches

#### Fastener Length:

1.940 inches

#### Head Style:

Double hexagon extended washer

**Head Height:** 

0.337 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

#### **Extended Washer Diameter:**

Between 0.715 inches and 0.725 inches

#### **Extended Washer Thickness:**

0.075 inches

### **Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

## **Thread Diameter:**

0.375 inches

## Grip Length:

Between 0.630 inches and 0.670 inches

#### Thready Qty Per Inch (tpi):

16

#### Min. Tensile Strength (psi):

260000 pounds per square inch

#### Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

#### Material:

Steel comp h11

#### Material Specification:

Ams 6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

## Thread Series Designator:

Unjc

#### Shelf Life:

N/a

# NSN 5306-01-209-7163

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

