

View Online at <https://aerobasegroup.com/nsn/5306-01-209-7856>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.120 inches

Eye Inside Diameter:

Between 1.120 inches and 1.250 inches

Shoulder Thickness:

Between 0.190 inches and 0.250 inches

Shank Length:

Between 1.500 inches and 1.620 inches

Eye Stock Diameter:

Between 0.440 inches and 0.500 inches

Shoulder Diameter:

Between 0.880 inches and 0.940 inches

Shank Unthreaded Hole Diameter:

0.139 inches and 0.144 inches first hole

Overall Length:

Between 3.810 inches and 4.190 inches

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

13

Distance From Center Of Eye To Shank End:

Between 2.810 inches and 3.060 inches

Eye Outside Width:

2.120 inches

Special Features:

Distance from largest bearing surface to shank hole center 1.340 in.

Material:

Steel

Material Specification:

Mil-b-45908 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-45908 spec.