

View Online at <https://aerobasegroup.com/nsn/5306-01-209-7873>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.450 inches

**Fastener Length:**

Between 1.348 inches and 1.378 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Shoulder Diameter:**

0.2802 inches and 0.2807 inches first shoulder

**Shoulder Length:**

0.928 inches and 0.948 inches first shoulder

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams 4967 comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6804 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0