

View Online at <https://aerobasegroup.com/nsn/5306-01-209-7950>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.305 inches and 0.372 inches

**Fastener Length:**

Between 1.627 inches and 1.674 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.140 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches and 0.075 inches first hole

**Head Minor Diameter:**

Between 0.383 inches and 0.389 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.506 inches and 1.563 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0