

View Online at <https://aerobasegroup.com/nsn/5306-01-209-9285>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.2755 inches and 0.4995 inches

Fastener Length:

Between 0.3755 inches and 0.4995 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.188 inches

Width Between Flats:

Between 0.4250 inches and 0.4375 inches

Thread Diameter:

0.250 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

74000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

57000 pounds per square inch

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541 or steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011

Material Specification:

Sae j429 assn standard all material responses

Thread Series Designator:

Unc

Specification Or Standard:

2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: