NSN 5306-01-209-9300

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-209-9300

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.589 inches and 0.639 inches |
| Fastener Length: |
| Between 2.099 inches and 2.129 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.378 inches and 0.398 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.449 inches |
| Extended Washer Diameter: |
| Between 0.639 inches and 0.649 inches |
| Extended Washer Thickness: |
| Between 0.081 inches and 0.101 inches |
| Shoulder Diameter: |
| 0.4052 inches and 0.4057 inches first shoulder |
| Shoulder Length: |
| 1.490 inches and 1.510 inches first shoulder |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Thread Diameter: |
| 0.375 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response |

NSN 5306-01-209-9300

Shoulder Bolt - Page 2 of 2

A003b0



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |