## NSN 5306-01-209-9302

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-209-9302

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.589 inches and 0.639 inches
Fastener Length:
Between 2.911 inches and 2.941 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.429 inches and 0.449 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Shoulder Diameter:
0.4052 inches and 0.4057 inches first shoulder
Shoulder Length:
2.302 inches and 2.312 inches first shoulder
Hole Diameter:
Between 0.050 inches and 0.060 inches
Thread Diameter:
0.375 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Shoulder Shape:
Round first shoulder
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response

## **NSN 5306-01-209-9302** Shoulder Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: