NSN 5306-01-209-9303

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-209-9303

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.680 inches and 0.730 inches **Fastener Length:** Between 1.752 inches and 1.782 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.425 inches and 0.445 inches Width Between Flats: Between 0.492 inches and 0.512 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches **Shoulder Diameter:** 0.4677 inches and 0.4682 inches first shoulder **Shoulder Length:** 1.052 inches and 1.072 inches first shoulder **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-209-9303

Shoulder Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0