NSN 5306-01-209-9348

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-209-9348

Thread Length:						
Between 0.475 inches and 0.525 inches						
Fastener Length:						
Between 0.797 inches and 0.827 inches						
Head Style:						
Double hexagon w/hole						
Head Height:						
Between 0.225 inches and 0.245 inches						
Width Between Flats:						
Between 0.305 inches and 0.313 inches						
Extended Washer Diameter:						
Between 0.465 inches and 0.475 inches						
Extended Washer Thickness:						
Between 0.032 inches and 0.052 inches						
Grip Diameter:						
Between 0.2485 inches and 0.2495 inches						
Thread Diameter:						
0.250 inches						
Grip Length:						
Between 0.302 inches and 0.322 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
200000 pounds per square inch						
Surface Finish:						
32.0 microinches threads						
Material:						
Iron alloy 660						
Material Specification:						
Ams 5737 assn standard single material response						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2, cl 2 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						
N/a						

NSN 5306-01-209-9348

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0