## NSN 5306-01-209-9375

Close Tolerance Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-209-9375



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.364 inches and 0.414 inches Fastener Length: Between 0.562 inches and 0.592 inches **Head Style:** Undercut hexagon **Head Height:** Between 0.110 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2490 inches and 0.2496 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ms 5737 assn standard single material response **Surface Treatment:** Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

---

## NSN 5306-01-209-9375

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0

