NSN 5306-01-210-0762

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-210-0762

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.526 inches and 0.576 inches **Fastener Length:** Between 0.661 inches and 0.691 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: Between 0.366 inches and 0.386 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Shoulder Diameter:** 0.3427 inches and 0.3432 inches first shoulder **Shoulder Length:** 0.115 inches and 0.135 inches first shoulder **Hole Diameter:** Between 0.050 inches and 0.060 inches **Thread Diameter:** 0.312 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon longitudinal hole **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response

NSN 5306-01-210-0762 Shoulder Bolt - Page 2 of 2

A003b0



| Surface Treatment: |
|---------------------------------------------------------|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |