

View Online at <https://aerobasegroup.com/nsn/5306-01-210-6244>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.680 inches and 0.730 inches

**Fastener Length:**

Between 2.440 inches and 2.470 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.425 inches and 0.445 inches

**Width Between Flats:**

Between 0.492 inches and 0.512 inches

**Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

**Extended Washer Thickness:**

Between 0.089 inches and 0.109 inches

**Shoulder Diameter:**

0.4677 inches and 0.4682 inches first shoulder

**Shoulder Length:**

1.740 inches and 1.760 inches first shoulder

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Thread Diameter:**

0.437 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0