## NSN 5306-01-211-0667

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-211-0667 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.627 inches and 0.677 inches **Fastener Length:** Between 2.387 inches and 2.417 inches **Head Style:** Hexagon **Head Height:** Between 0.438 inches and 0.453 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Shank Unthreaded Hole Diameter:** 0.141 inches and 0.151 inches first hole **Concentric Hole Diameter:** Between 0.640 inches and 0.649 inches **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): 14 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.243 inches and 2.293 inches first hole **Special Features:** Concentric hole painted; color white fed-std-595 color no. 17875 Material: Titanium alloy **Material Specification:** Ams4967 assn standard single material response or ams4928 assn standard single material response **Surface Treatment:** Paint head **Surface Treatment Specification:** Lc+86-1546 fscm 36659 mfr ref single treatment response head **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5306-01-211-0667

Internally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0