

View Online at <https://aerobasegroup.com/nsn/5306-01-211-1445>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.680 inches and 0.730 inches

Fastener Length:

Between 1.940 inches and 1.970 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.425 inches and 0.445 inches

Width Between Flats:

Between 0.492 inches and 0.512 inches

Extended Washer Diameter:

Between 0.740 inches and 0.750 inches

Extended Washer Thickness:

Between 0.089 inches and 0.109 inches

Shoulder Diameter:

0.4677 inches and 0.4682 inches first shoulder

Shoulder Length:

1.240 inches and 1.260 inches first shoulder

Thread Diameter:

0.437 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0