

View Online at <https://aerobasegroup.com/nsn/5306-01-211-4339>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.589 inches and 0.639 inches

**Fastener Length:**

Between 3.161 inches and 3.191 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.378 inches and 0.398 inches

**Width Between Flats:**

Between 0.429 inches and 0.449 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Shoulder Diameter:**

0.4052 inches and 0.4057 inches first shoulder

**Shoulder Length:**

2.552 inches and 2.572 inches first shoulder

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0