## NSN 5306-01-212-4526

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-212-4526 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.600 inches **Fastener Length:** 0.750 inches **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches First Diameter From Head: Between 0.079 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.150 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.093 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5306-01-212-4526

Internal Wrenching Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0