

View Online at <https://aerobasegroup.com/nsn/5306-01-212-4533>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.640 inches

Fastener Length:

2.522 inches

Shoulder Diameter:

Between 0.4985 inches and 0.4995 inches

Shoulder Length:

Between 1.802 inches and 1.812 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches first hole

Concentric Hole Depth:

1.592 inches

Concentric Hole Diameter:

0.310 inches

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.292 inches first hole

Special Features:

Concentric hole finish polyurethane per mil-c-83286, color gray no. 36320

Material:

Steel comp 4130 or steel comp 4140

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response

Surface Treatment:

Plastic top of head

Surface Treatment Specification:

Qq-c-320, ty1, cl1 military specification single treatment response grip

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.