NSN 5306-01-212-6123

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-212-6123

Qq-p-416, type 2 class 3 federal specification single treatment response

The state of the s
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.499 inches and 0.578 inches
Fastener Length:
Between 3.015 inches and 3.062 inches
Head Style:
Hexagon
Head Height:
Between 0.203 inches and 0.234 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
Between 0.065 inches and 0.075 inches
Thread Diameter:
0.250 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Special Features:
Between drill concentric hole in head 0.188 diameter and 0.151 and 0.182 maximum in length
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Material Specification:
Mil-b-6812 military specification all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

NSN 5306-01-212-6123

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Deminiarization.
No

Mil-std (military Standard):

Mil-b-6812 spec.