NSN 5306-01-212-6124

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-212-6124

View Online at https://aerobasegroup.com/nsn/5306-01-212-6124
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 2.704 inches and 2.734 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Shoulder Diameter:
0.3735 inches and 0.3745 inches first shoulder
Shoulder Length:
2.240 inches and 2.260 inches first shoulder
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
rinoddy ety i or mon (tpi).
24
24
24 Min. Tensile Strength (psi):
24 Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 3 federal specification single treatment response
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 3 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 3 federal specification single treatment response Thread Series Designator: Unf
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Material Specification: Mil-b-7838 military specification all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 3 federal specification single treatment response Thread Series Designator: Unf Shelf Life:

--

NSN 5306-01-212-6124

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-7838 spec.