## NSN 5306-01-212-7843

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-212-7843

·
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.860 inches
Fastener Length:
1.845 inches
Head Style:
Double hexagon w/hole
Head Height:
0.504 inches
Width Between Flats:
0.648 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
0.123 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
0.985 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 42.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, ty2, cl1 military specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-212-7843

Shear Bolt - Page 2 of 2



Shelf L	ife:
---------	------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.