

View Online at <https://aerobasegroup.com/nsn/5306-01-213-2460>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.553 inches

**Fastener Length:**

0.625 inches

**Head Diameter:**

Between 0.303 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Hole Diameter:**

0.005 inches

**First Diameter From Head:**

Between 0.157 inches and 0.167 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.088 inches and 0.148 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.159 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Round longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 410

**Material Specification:**

Hs178, fscm 73030 mfr ref single material response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0